

FORM OF SHORT QUOTATION NOTICE

Government Engineering College Thrissur

D2/1232/23/GECTCR

21.02.2023

Sealed quotations are invited for the supply of the Autoclave Turbidity standard for chemical engg. department of this institution:

Separate List attached

The envelopes containing the quotation should bear the superscription "Qtn. No.D2/93/22-23 due on 07/03/2023" and should be addressed to the Principal, Govt. Engg. College, Thrissur, Kerala. Intending tenderers may submit the quotations on their own papers.

Last date for receipt of quotations is 07/03/2023 2.00pm Late quotations will not be accepted. The quotations will be opened at 02.00 pm on 08/03/2023 in the presence of such of the quotationers or their authorized representatives who may be present at that time. The maximum period required for delivery of the articles should also be mentioned.

Details of the requirements and the conditions governing their supply can be obtained free on request from Principal, Govt. Engg. College, Thrissur, Kerala. till 07/03/2023 2 pm

Place:Thrissur


Dr. Ranjini Bhattathiripad T

Principal

copy to

- 1.Dr. Padmavathy K S,AP CHE Department
- 2.Office
- 3.Notice board

Forwarded/By Order


Accounts Officer

ITEM DESCRIPTION

| SL No | Item with specification | Quantity Required |
|-------|---|-------------------|
| 1 | <p>Rotek Vertical Autoclave Model RAV-03-SS(Size:300*500mm,volume:35Ltr,Power 2KW)</p> <p>The vertical steam sterilizer is used for sterilizing the loaded material under steam pressure of 15-20PSI. Double walled construction, inner and outer body made of heavy gauge stainless steal 304 quality sheets, duly argon arc welded. The lid and ring are made up of stainless steal plate. The lid is fitted with pressure gauge, safety (adjustable spring loaded)and steam exhaust valve ,provided safety valves set to blow of at 15PSI.A silicon rubber gasket is fitted in ring to ensure steam tight joint of the lid Foot operated lifting mechanism for lid opening. Electrically operated, ISI quality immersion type heaters are used for heating. The Autoclave is supported with three sturdy legs duly painted, supplied with cord and plug, Stainless steel perforated basket.</p> <p><u>Optional Features</u></p> <ol style="list-style-type: none"> 1. Digital temp: controller cum indicator, 2. Digital timer with indicator, 3. Auto pressure cut off system, 4. Automatic water level cut off system, 5. Water level indicator with glass tube, 6. Auto purging and exhaust with solenoid valve | 1 Unit |

Approval Valid

Digitally Approved By

Dr Ranjini Bhattathiripad T *

Date: 21.02.2023

Reason: Approved